



## Supplier of DIN1629 Steel Pipes Manufacturing Pipeline PipeLine

Professional Manufacturer and Supplier from China specialized in Steel Pipes Manufacturing Pipeline PipeLine and Pipe Fittings at consistant quality



[Contact Now](#)

### Features Specifications:

OD(mm)	Wall Thickness Unit(mm)													
	2	2.5	3	3.5	4	4.5	5	6	6.5-7	7.5-8	8.5-9	9.5-10	11	12
Φ25-Φ28	•	•	•	•	•	•								
Φ32		•	•	•	•	•	•							
Φ34-Φ36		•	•	•	•	•	•							
Φ38		•	•	•	•	•	•							
Φ40			•	•	•	•	•							
Φ42			•	•	•	•	•							
Φ45			•	•	•	•	•	•						
Φ48-Φ60			•	•	•	•	•	•	•					
Φ63.5				•	•	•	•	•	•	•				
Φ68-Φ73					•	•	•	•	•	•				
Φ76					•	•	•	•	•	•	•	•	•	•
Φ80					•	•	•	•	•	•	•	•	•	•
Φ83					•	•	•	•	•	•	•	•	•	•
Φ89					•	•	•	•	•	•	•	•	•	•
Φ95					•	•	•	•	•	•	•	•	•	•
Φ102					•	•	•	•	•	•	•	•	•	•
Φ108					•	•	•	•	•	•	•	•	•	•
Φ114						•	•	•	•	•	•	•	•	•
Φ121							•	•	•	•	•	•	•	•
Φ127								•	•	•	•	•	•	•
Φ133									•	•	•	•	•	•
Φ140										•	•	•	•	•
Φ146											•	•	•	•
Φ152												•	•	•
Φ159													•	•
Φ168														•



seamless steel tubes for pressure purposes	
<b>Application:</b>	It is used for manufacturing pipeline,vessel,equipment,pipe fittings
<b>Size(mm):</b>	O.D.:6.0~219.0 W.T.:1~30 L:max 12000

**steel,chemical composition(DIN1629):**

Standard	Grade	Chemical Composition							Mechanical Property		
		C	Si	Mn	P≤	S≤	Cr	Mo	MPa)	(MPa)	(%)
DIN1629	St35.8/St37.5	≤0.17	/	/	0.04	0.04	/	/	350~480	≥235	≥25
	St52.0/St52.3	≤0.22	≤0.55	≤0.17	0.04	0.04	/	/	500~560	≥270	≥21

**steel,chemical composition(EN10216-1):**

Standard	Grade	Chemical Composition							Mechanical Property			
		C	Si	Mn	P≤	S≤	Cr≤	Mo	(MPa)	(MPa)	L	t
EN10216-1	P195TR1	≤0.13	≤0.35	≤0.70	0.025	0.020	0.30	≤0.08	320~440	≥195	≥27	≥25
	P235TR1	≤0.16	≤0.35	≤1.20	0.025	0.020	0.30	≤0.08	360~500	≥235	≥25	≥23
	P265TR1	≤0.20	0.40	1.40	0.025	0.020	0.30	≤0.08	410~570	≥265	≥23	≥19

